

Information Bulletin No. 21

Cold Treatment Demulsifiers for Used Oil

Introduction

Several new ECO* formulations are presented to oil recyclers and waste oil generators. Especially effective on high-water, high-surfactant used oils, these products work at ambient temperature, show rapid water drop and “wash” solids out of the oil. Naturally, they also perform at elevated temperatures, where you may expect a dosage of 1000-2000 ppm, instead of 2000-3000 ppm.

Applications

Demulsifier	Primary Application	Other Successes
ECO 16SP	Railroad Oils	High-water lube oils; spent metal-working coolants; de-hazing of fuels.
ECO 22-4BC ECO 24 ECO 80	Crankcase Oils	“Rag” oils; high-water lube oils; crude slops.
ECO 33 ECO 33BC ECO 33-60BC	Lube Line Flushes	Railroad oils; high-water industrial oils; fuel/bunker oils.
ECO 70BC	Crankcase Oils	Refinery slops; fuel tank bottoms; fuel/bunker oils.
ECO 47 ECO53 ECO 53BC ECO 53-60BC	Railroad Oils	High-water industrial oils; tramp oils; petrochemical wastes; fuel tank bottoms .

**Trademark of Emulsions Control, Inc.*

Emulsions Control, Inc. 925 Hale Place, # A7, Chula Vista, CA 91914; Tel (619) 656-8899; Fax (619) 656-8895